



MATERIAL: EPOXY RESIN BONDED GLASS FIBRE LAMINATE SHEET TO BS.4584 Pt.3 TYPE FR4. MATERIAL MUST CONFORM TO UL94V-0. COPPER PLATING TO BE 1oz MIN (35um) FINISHED THICKNESS 1.6mm / 1/16". DOUBLE-SIDED COPPER. BOARD SIZE 130.0mm BY 40.5mm.

FINISH: ALPHA LEVEL SILVER
SOLDER RESIST REQUIRED ON SOLDER SIDE
SILKSCREEN IN WHITE

LAYER BUILD

=====	TOP SILK SCREEN
=====	COMMON SOLDER RESIST
=====	COMPONENT SIDE COPPER
=====	=====
=====	SOLDER SIDE COPPER
=====	COMMON SOLDER RESIST

HOLE DATA TABLE			
REF.	FINISHED DIA - mm	QUANTITY	PLATED
A	0.8	5	YES
B	1.1	22	YES
C	6.5	2	YES
D	6.5	4	YES
E			
UNREF	1.0	60	YES

Baldwin PCB Design		mike@baldwinpcbdesign.co.uk	
		01825 762100	
Customer			
PETER PERKINS			
Title			
BMS Slave V2.00		1	14/08/08
BMS SLAVE BOARD V2.00		Issue	Date